

IN THE CLAIMS:


Please rewrite the claims as follows:

1. (original) A method of calculating a sampling function for fabricating a N-channel grating, the method comprising the steps of :
 - forming a summation of N periodic seeding functions each describing a refractive index variation, wherein each periodic function includes a phase shift value with respect to the other functions, and wherein at least one phase shift value is non-zero.
2. (original) A method as claimed in claim 1, wherein the summation of the N periodic functions comprises a Fourier analysis.
3. (original) A method as claimed in claim 2, wherein the result of the Fourier analysis is expressed as: $\sum_{l=1}^N \kappa e^{i[K_0 z + \theta + (2l-N-1)\Delta\kappa z / 2 + \phi_l]} = \kappa Q e^{i(K_0 z + \theta + \psi)}$.
4. (original) A method as claimed in ~~any one of claims claim 1 to 3~~, wherein the method further comprises the step of determining a set of the phase shift values for which a maximum value of the sampling function amplitude is minimised.
5. (currently amended) A method as claimed in ~~any one of claims claim 1 to 3~~, wherein the method further comprises the step of determining a set of the phase shift values for which a maximum difference between a maximum and minimum value of the sampling function amplitude is minimised.
6. (currently amended) A method as claimed in ~~any one of claims claim 1 to 3~~, wherein the method further comprises the step of determining a set of the phase shift values for which a mean-square- deviation in the sampling function is minimised.
7. (currently amended) A method as claimed in ~~any one of claims claim 4 to 6~~, wherein the step of determining the set of phase shift values comprises direct scanning through all combinations, or conducting a variational analysis, or using other forms of extremum search numerical techniques, or a simulated annealing Monte Carlo approach.

8. (currently amended) A method as claimed in ~~any one of the preceding claims~~ claim 1, wherein the grating is multi-dimensional, and wherein the periodic seeding functions are multi-dimensional.
9. (currently amended) A method for fabricating a multi-channel grating comprising the step of calculating a sampling function in accordance with a method as claimed in ~~any one of~~ claims claim 1 to 8.
10. (original) A method as claimed in claim 9, wherein the multi-channel grating is fabricated utilising photo-induced refractive index changes in a photosensitive waveguide material.
11. (original) A method as claimed in claim 9, wherein the multi-channel grating is fabricated utilising etching techniques.
12. (original) A method as claimed in claim 9, wherein the multi-channel grating is fabricated utilising epitaxial techniques.
13. (original) A method as claimed in claim 9, wherein the multi-channel grating is fabricated utilising a developing technique.
14. (original) A method as claimed in claim 13, wherein the developing technique comprises a photo polymerisation process.
15. (currently amended) A multi-channel grating structure fabricated utilising a method of fabrication as claimed in ~~any one of claims~~ claim 9 to 14.

Respectfully submitted,

Date: December 12, 2003


 Dion M. Brehman
 for Michael J. Lyons
 PENNIE & EDMONDS LLP
 3300 Hillview Avenue
 Palo Alto, California 94304
 (650) 493-4935

45,645
 (Reg. No.)
37,386